



GLOBAL WINDOW FILMS

SPECIALTY

SPECIALTY Solar Performance Specifications

SPECIALTY - Solar Performance Specifications														
	Solar Energy			Visible Light				UVR	SC	SHR	TSER	GR	E	U-Value
	T	A	R	T	A	R								
						Int	Ext							
Silver Matte	15	38	47	19	27	38	54	99	.29	71	75	79	.70	1.05
Bronze Matte	56	38	6	35	58	9	7	98	.77	23	33	61	.86	1.14
Grey Matte	55	38	7	36	57	9	7	98	.78	22	34	60	.86	1.14
White Matte	61	31	8	77	14	9	9	97	.81	19	30	14	.85	1.09
Black Out	0	59	41	0	96	3	4	99	.18	82	85	100	.63	1.00
UV Clear	81	13	6	89	5	6	6	99	.98	2	15	1	.86	1.15
Blue 35	55	38	7	38	55	5	7	99	.76	24	34	58	.86	1.14
Yellow 80	72	22	6	83	10	7	7	99	.90	10	22	8	.89	1.13
Red 20	59	35	6	23	73	4	4	99	.80	20	31	74	.89	1.13

SPECIALTY Construction and Availability Specifications

SPECIALTY - Construction and Availability							
	100' Rolls		Adhesive		SRC	Ply	Mil
Silver Matte	60"		PS		No	2	2
Bronze Matte	60"		PS		No	1	2
Grey Matte	60"		PS		No	1	2
White Matte	60"		PS		No	1	2
Black Out	60"		PS		Yes	3	2.5
UV Clear	60"		PS		Yes	2	2
Blue 35	60"		PS		Yes	1	1
Yellow 80	60"		PS		Yes	1	1
Red 20	60"		PS		Yes	1	1